

Designed to offer an exceptional weight/power/size ratio, the ABITIG 260W torch is highly manoeuvrable giving less fatigue to the user. The molded handle provides optimal grip to achieve the perfect weld.

FEATURES

260 W GRIP

Cooling: Liquid

Capacity:

- direct current (DC): 260 A

- in alternating current (AC): 185 A

Duty cycle: 100%

Tungsten electrode: Ø 1.0 - 3.2 mm



CONFIGURATIONS



Connector		AMPHENOL	l (m)	Ref
Ø 35/50			4 m	039346
			8 m	039353



Trigger

CONSUMABLES

Nozzle



N2 - Ø8.0	(x5)	039438
N3 - Ø10.0	(x5)	039391

Standard insulating ring



Nous consulter

Electrode holder



Ø 1.6	(x3)	039360
Ø 2.0	(x3)	039377
Ø 2.4	(x3)	039384
Ø 3.2	Nous consulter	

head cover



Courte	(x1)	039407
Longue	(x1)	044746

STANDARD ASSEMBLY

RECOMMANDATIONS

	TIG 160 DC	TIG 168 DC	TIG 200 DC FV	TIG 220 DC FV	TIG 300 DC	TIG 207 AC/DC FV	TIG 208 AC/DC	TIG 220 AC/DC	TIG 250 AC/DC
260 W connection 35/50 + AMPHENOL	-	-	-	✓	✓	-	-	✓	✓