

The air-cooled MIG/MAG welding torches meet the needs of welders for a wide range of welding tasks. The GRIP handle's anti-slip coating and new ball joint provide you with exceptional working comfort.

### DESCRIPTION

Extremely resistant torch.  
For industrial bodywork and boiler making.  
New ergonomic handle with «GRIP» coating ensures a secure grip even in difficult positions.

### FEATURES

- **Max current (Imax):** 340 A: CO2 and 290 A: Ar/CO2  
*In pulsed mode, these capacities are reduced by 35%*
- **Duty cycle:** 290 A @ 60 %
- **Recommended wire diameters:** 0.8 to 1.2 mm
- **Lengths:** 3 m & 4 m



### CONSUMABLES

#### Torch



#### Contact tube supports & diffusers

	STEEL	ALU		STEEL	ALU
	043008			042926	

#### Contact tubes

	STEEL	ALU
Ø 0.8	041790	-
Ø 1.0	419803	419766
Ø 1.2	419810 ●●	419773 ●●
Ø 1.4	419827	-
Ø 1.6	419834	041080

#### Nozzles

	STEEL	ALU
Ø 16	041783 ●	041783 ●

#### Sheath

	Ø 0.6/0.8		Ø 1.0 & 1.2		Ø 1.2 & 1.6	
	3 m	4 m	3 m	4 m	3 m	4 m
Steel	041592	041837	041608 ●	041844 ●	418417	418424
Teflon	041578	044050	041585	044067	-	044074
Carbon	-	039834	-	039827	-	039810

#### Consumables box option:

Ref. 041417

	x2
	x3
	x5 (M8-Ø 1.0)
	x5 (M8-Ø 1.2)
	x5 (Alu-M8-Ø 1.0)
	x5 (Alu-M8-Ø 1.2)
	x3



● Original steel equipment 3 m  
● Original aluminium equipment 3 m

● Original steel equipment 4 m  
● Original aluminium equipment 4 m